

**Amendments to the Claims:**

Please amend the claims to agree with the following listing thereof:

1. (Cancelled).

2. (Currently amended) A sampling circuit for an analog signal according to a clock signal, comprising:

a first thin film transistor (TFT), having a first electrode to receive the analog signal, a control electrode to receive the clock signal and a second electrode for sampling the analog signal when the clock signal is at a first logic level; and

The circuit as claimed in claim 1, wherein the counteracting device is a capacitor between the second electrode and a reference potential node;

wherein a feed-through voltage drop caused by a parasitic capacitor between the second electrode and the control electrode of the first TFT is determined according to the value of the capacitor; and

wherein when the clock signal is changed from the first logic level to a second logic level, the capacitor reduces the feed-through voltage drop.

3. (Cancelled)

4. (Currently amended) A sampling circuit for an analog signal according to a clock signal, comprising:

a first thin film transistor (TFT), having a first electrode to receive the analog signal, a control electrode

to receive the clock signal and a second electrode for sampling the analog signal when the clock signal is at a first logic level; and

a counteracting device coupled to the second electrode and comprising:

an inversion device, having an input terminal coupled to the control electrode; and

~~The circuit as claimed in claim 3, wherein the capacitor comprises a second TFT having a gate terminal coupled to an the output terminal of the inversion device and a source and drain terminal both coupled to the second electrode;~~

wherein when the clock signal is changed from the first logic level to a second logic level, the counteracting device reduces a feed-through voltage drop caused by a parasitic capacitor between the second electrode and the control electrode of the first TFT.

5. (Cancelled)

6. (Currently amended) A liquid crystal display, comprising:

a plurality of display units, arranged in an array;  
a plurality of data lines disposed corresponding to each line of the display units, wherein each data line provides a video signal to the corresponding display unit; and  
a data driving circuit, having at least one sampling circuit, sampling an image signal to be the

video signal according to a clock signal, and  
the sampling circuit comprising:

a first thin film transistor (TFT), having a first  
electrode receiving an analog signal, a control  
electrode receiving the clock signal, and a second  
electrode for sampling the analog signal when the clock  
signal is at a first logic level; and

~~The liquid crystal display as claimed in claim 5,~~  
~~wherein the counteracting device is a capacitor between~~  
~~the second electrode and a reference potential node;~~

wherein a feed-through voltage drop caused by a  
parasitic capacitor between the second electrode and  
the control electrode of the first TFT is determined  
according to the value of the capacitor; and

wherein when the clock signal is changed from the  
first logic level to a second logic level, the  
capacitor reduces the feed-through voltage drop.

7. (Cancelled)

8. (Currently Amended) A liquid crystal display,  
comprising:

a plurality of display units, arranged in an array;  
a plurality of data lines disposed corresponding to  
each line of the display units, wherein each  
data line provides a video signal to the  
corresponding display unit; and  
a data driving circuit, having at least one sampling  
circuit, sampling an image signal to be the

video signal according to a clock signal, and  
the sampling circuit comprising:

a first thin film transistor (TFT), having a first  
electrode receiving an analog signal, a control  
electrode receiving the clock signal, and a second  
electrode for sampling the analog signal when the clock  
signal is at a first logic level; and

a counteracting device coupled to the second  
electrode and comprising:

an inversion device, having an input terminal  
coupled to the control electrode; and

~~The liquid crystal display as claimed in claim 7,~~  
wherein ~~the capacitor comprises~~ a second TFT having a  
gate terminal coupled to an ~~the~~ output terminal of the  
inversion device and a source and drain terminal, both  
coupled to the second electrode;

wherein when the clock signal is changed from the  
first logic level to a second logic level, the  
counteracting device reduces a feed-through voltage drop  
caused by a parasitic capacitor between the second  
electrode and the control electrode of the first TFT.